

## FEATURES

### TRUE TRIPLE ANGLE OPERATION

- 20°** High gloss surfaces such as automotive paint finish, polished metals and plastics
- 60°** Universal gloss measurement angle for all applications
- 85°** Matt surfaces such as automotive interiors, architectural paints and wood finishes
- 20°/60°/85°** Measure or calibrate all three angles simultaneously

### CONTINUOUS READ

Assess gloss variations on a large surface in seconds

### FLEXIBLE CALIBRATION

Calibrate on a standard that matches your sample for improved gloss control. Additional standards available from matt to mirror finish

### STATISTICAL ANALYSIS

Automatic calculation of batch statistics

### USB DOWNLOAD OF DATA

Download your results to Novo-Soft for further analysis, reporting and storage

## EXTRAS

### FREE EXTENDED WARRANTY

Register for a two year comprehensive guarantee

### FREE LIGHT SOURCE WARRANTY

Guaranteed for the life of the instrument

### UKAS CALIBRATION

Instruments and calibration tiles are available with ISO 17025 certification

### CALIBRATION AND SERVICE

Fast and economic service via our global network of accredited calibration and service centres

## ACCESSORIES

- Integrated BAM traceable calibration standard
- Calibration tile cleaning kit
- Quick-start guide
- USB cable
- Protective instrument case
- 4 x AA high power batteries
- Novo-Soft™ QA software CD
- Full instruction manual in PDF format
- Screwdriver



## SPECIFICATIONS

Resolution	0.1GU
Repeatability	0.1%
Reproduceability	0.5%
Battery life	15,000+ readings
Languages	EN, FR, D, NL, ESP, IT, TK, CZ

## CONFORMITY

International standards:

- BS EN ISO 2813
- ASTM D523
- ASTM D2457
- DIN 67530
- JIS 8741



Certificate no: FM 29741  
BS EN ISO 9001: 2000

LOCAL AGENT



Beeching Road, Bexhill-on-Sea, East Sussex, TN39 3LG, UK  
T +44 (0) 1424 214291 F +44 (0) 1424 730600  
enquiries@rhopointinstruments.com www.rhopointinstruments.com